

SIMATIC PS307/1AC/24VDC/10A
 SIMATIC S7-300 Regulated power supply PS307 input: 120/230 V
 AC, output: 24 V / 10 A DC



Input	
Input	1-phase AC
• Note	Automatic range selection
supply voltage	
• 1 at AC rated value	120 V
• 2 at AC rated value	230 V
input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	170 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering	at $V_{in} = 93/187$ V
Mains buffering at lout rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 120 V	4.2 A
• at rated input voltage 230 V	1.9 A

Switch-on current limiting (+25 °C), max.	55 A
duration of inrush current limiting at 25 °C	
• maximum	3 ms
I ² t, max.	3.3 A ² ·s
Built-in incoming fuse	T 6.3 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C

Output

Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	50 mV
Residual ripple peak-peak, typ.	15 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	60 mV
product function output voltage adjustable	No
Output voltage setting	-
Status display	Green LED for 24 V OK
On/off behavior	No overshoot of V _{out} (soft start)
Startup delay, max.	2 s
Voltage rise, typ.	10 ms
Rated current value I _{out} rated	10 A
Current range	0 ... 10 A
supplied active power typical	240 W
short-term overload current	
• on short-circuiting during the start-up typical	38 A
• at short-circuit during operation typical	38 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	80 ms
• at short-circuit during operation	80 ms
Parallel switching for enhanced performance	Yes

Efficiency

Efficiency at V _{out} rated, I _{out} rated, approx.	90 %
Power loss at V _{out} rated, I _{out} rated, approx.	27 W

Closed-loop control

Dynamic mains compensation (V _{in} rated ±15 %), max.	0.1 %
Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ.	2 %
setting time maximum	0.1 ms

Protection and monitoring	
Output overvoltage protection	Additional control loop, shutdown at < 28.8 V, automatic restart
Current limitation	11 ... 12 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current RMS value	
• maximum	12 A
Overload/short-circuit indicator	-

Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.6 mA
Degree of protection (EN 60529)	IP20

Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289
Explosion protection	ATEX (EX) II 3G Ex nA II T4; cULus (ANSI/ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
certificate of suitability NEC Class 2	No
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	No
Marine approval	In S7-300 system

EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

environmental conditions	
ambient temperature	
• during operation	0 ... 60 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics	
Connection technology	screw-type terminals
Connections	

<ul style="list-style-type: none"> • Supply input 	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
<ul style="list-style-type: none"> • Output 	L+, M: 4 screw terminals each for 0.5 ... 2.5 mm ²
<ul style="list-style-type: none"> • Auxiliary 	-
width of the enclosure	80 mm
height of the enclosure	125 mm
depth of the enclosure	120 mm
required spacing	
<ul style="list-style-type: none"> • top 	40 mm
<ul style="list-style-type: none"> • bottom 	40 mm
<ul style="list-style-type: none"> • left 	0 mm
<ul style="list-style-type: none"> • right 	0 mm
Weight, approx.	0.8 kg
product feature of the enclosure housing can be lined up	Yes
Installation	Can be mounted onto S7 rail
mechanical accessories	Mounting adapter for standard mounting rail (6EP1971-1BA00)
MTBF at 40 °C	1 504 280 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)